

# CABLE PROTECTOR REFERENCE GUIDE

		MODEL NO.	CHANNEL HEIGHT	LOAD CAPACITY (PER AXLE)	# OF CHANNELS	PAGE	
<b>T-Connector</b>	Linebacker Heavy Duty 5-Channel	CP5X125	1.35 in. (3.43 cm)	40,300 lb. (18,280 kg)	5	6	
	Linebacker Heavy Duty 4-Channel	CP4X125	1.35 in. (3.43 cm)	40,300 lb. (18,280 kg)	4	8	
	Linebacker Heavy Duty 3-Channel	CP3X225	2.25 in. (5.72 cm)	28,420 lb. (12,892 kg)	3	10	
	Linebacker Heavy Duty 2-Channel	CP2X325	3.25 in. (8.27 cm)	21,760 lb. (9,870 kg)	2	12	
	Linebacker General Manufacturing 4-Channel	CP4X300	3 in. (7.62 cm)	20,200 lb. (9,163 kg)	4	13	
	Linebacker General Purpose 5-Channel	CP5X125-GP	1.3 in. (3.3 cm)	21,000 lb. (9,526 kg)	5	14	
	Linebacker General Purpose Drop Over/Split Top 1.25" Height	CP1X125	1.25 in. (3.18 cm)	23,400 lb. (10,614 kg)	1	16	
	Linebacker General Purpose Drop Over/Split Top 2.25" Height	CP1X225	2.25 in. (5.72 cm)	17,000 lb. (7,712 kg)	1	16	
	<b>Dog Bone Connector</b>	Yellow Jacket Heavy Duty 5-Channel	YJ5-125	1 in. (2.54 cm)	32,600 lb. (14,787 kg)	5	18
		Yellow Jacket Heavy Duty 5-Channel ADA	YJ5-125-ADA	1.325 in. (3.37 cm)	21,000 lb. (9,526 kg)	5	20
Yellow Jacket Heavy Duty 4-Channel		YJ4-125	1.25 in. (3.18 cm)	32,600 lb. (14,787 kg)	4	21	
Yellow Jacket Heavy Duty 3-Channel		YJ3-225	2.125 in. (5.4 cm)	28,420 lb. (12,892 kg)	3	22	
Yellow Jacket Heavy Duty 5-Channel - 3.75" Channel		YJ5-400	3.75 in. (9.53 cm)	15,980 lb. (7,248 kg)	5	24	
Yellow Jacket Heavy Duty 2-Channel		YJ2-400	3.75 in. (9.53 cm)	15,980 lb. (7,248 kg)	2	24	
Yellow Jacket Heavy Duty 1-Channel 5" Height		YJ1-500	5 in. (12.7 cm)	18,780 lb. (8,518 kg)	1	25	
Yellow Jacket Heavy Duty 1-Channel 3" Height		YJ1-300	3 in. (7.62 cm)	15,980 lb. (7,248 kg)	1	25	
Yellow Jacket Heavy Duty 5-Channel AMS System		YJ5-125-AMS	1.25 in. (3.18 cm)	32,600 lb. (14,787 kg)	5	26	
Yellow Jacket Heavy Duty 3-Channel AMS System		YJ3-225-AMS	2.25 in. (5.72 cm)	28,420 lb. (12,892 kg)	3	27	
<b>Dog Bone Connector</b>		Guard Dog General Purpose 5-Channel	GD5X125	1.325 in. (3.37 cm)	21,000 lb. (9,526 kg)	5	28
		Guard Dog General Purpose 5-Channel ADA	GD5X125-ADA	1.325 in. (3.37 cm)	21,000 lb. (9,526 kg)	5	30
		Guard Dog General Purpose 3-Channel	GD3X225	2.25 in. (5.8 cm)	28,420 lb. (12,892 kg)	3	31
	Guard Dog General Purpose Drop Over 3-Channel	GD3-DO	1.325 in. (3.37 cm)	21,000 lb. (9,526 kg)	3	34	
	Guard Dog Low Profile 5-Channel	GD5X75-ST	0.75 in. (1.9 cm)	48,000 lb. (21,772 kg)	5	32	
	Guard Dog Low Profile 5-Channel w/ ADA Ramps	GD5X75	0.75 in. (1.9 cm)	68,000 lb. (30,844 kg)	5	32	
	Guard Dog Low Profile 3-Channel	GD3X75-ST	0.75 in. (1.9 cm)	34,000 lb. (15,422 kg)	3	32	
	Guard Dog Low Profile 3-Channel w/ ADA Ramps	GD3X75	0.75 in. (1.9 cm)	54,000 lb. (24,492 kg)	3	32	
	Guard Dog Low Profile 2-Channel	GD2X75-ST	0.75 in. (1.9 cm)	26,000 lb. (11,792 kg)	2	33	
	Guard Dog Low Profile 2-Channel w/ ADA Ramps	GD2X75	0.75 in. (1.9 cm)	46,000 lb. (20,864 kg)	2	33	
	Guard Dog Low Profile 1-Channel	GD1X75-ST	0.75 in. (1.9 cm)	26,000 lb. (11,792 kg)	1	33	
	Guard Dog Low Profile 1-Channel w/ ADA Ramps	GD1X75	0.75 in. (1.9 cm)	46,000 lb. (20,864 kg)	1	33	
	<b>T-Connector or Dog Bone Connector</b>	Bumble Bee Light Duty 5-Channel with T-Connectors	BB5-125-T	1.25 in. (3.18 cm)	12,000 lb. (5,444 kg)	5	36
		Bumble Bee Light Duty 5-Channel with Dog Bone Connectors	BB5-125-D	1.25 in. (3.18 cm)	12,000 lb. (5,444 kg)	5	36
<b>Gripper Connector</b>	Grip Guard Lightweight 5-Channel	GG5X125	1.25 in. (3.18 cm)	10,000 lb. (4,534 kg)	5	37	
<b>L-Connector</b>	FastLane Lightweight 1-Channel Drop Over	FL1X4	1 in. (2.54 cm)	2,100 lb. (954 kg)	1	39	
	FastLane Lightweight 2-Channel Drop Over	FL2X1.75	1 in. (2.54 cm)	2,100 lb. (954 kg)	2	39	
	FastLane Lightweight 1-Channel Drop Over	FL1X1.5	0.50 in. (1.27 cm)	2,100 lb. (954 kg)	1	39	



T-Connector



Dog Bone Connector



Gripper Connector



L-Connector